





Everest III & 600 Printer Specifications

Specification	Everest 600	Everest III
Printing Speed (For CMY color coverage)	60 seconds or less  Note: The first print takes 5 minutes, which includes warm-up time.	Normal mode: 60 seconds Best mode: 78 seconds  Note: The first print takes 5 minutes, which includes warm-up time.
Printing Modes	Monochrome and CMY	Monochrome, CMY, and CMY + W
Print Quality	Equivalent of 600 pixels per inch.	Equivalent of 300 pixels per inch.
Media Requirements	Use Rimage Media Kits™ for optimum recording and print performance.	Use Rimage Media Kits™ for optimum recording and print performance.
Print Ribbon Requirements	Monochrome (Black) CMY (Cyan, Magenta, and Yellow)	Monochrome (Black) CMY (Cyan, Magenta, and Yellow) CMY+W (Cyan, Magenta, Yellow, and White)
Ribbon Capacity	Monochrome Ribbon: 1000 discs CMY Ribbon: 500 discs Retransfer Ribbon: 1000 discs	Monochrome Ribbon: 1000 discs CMY Ribbon: 500 discs CMY+W Ribbon: 375 discs Retransfer Ribbon (standard): 1000 discs Retransfer Ribbon (optional): 500 discs
Physical Size	9.7" H x 9.4" W x 14.8" D (24.6 cm x 24.0 cm x 37.5 cm) Depth with print tray extended: 22.25" (56.5 cm) Left side cover open for print ribbon replacement – add additional 9" (23 cm) Weight: 40.8 lbs (18.5 kg) Weight with packaging: 50.7 lbs (23.0 kg)	
Interface	USB 2 (Universal Serial Bus) – B type connector	
Power	100 – 120V 500W or 220 – 240V 500W 50 / 60 Hz (manual switching)	
Operating Conditions	Temperature 59° to 86° F (15° to 30° C) Humidity 30% to 80%, non-condensing	
Printer Storage Requirements	Temperature -13° to 104° F (-25°C to 50° C) Humidity Up to 90%  Note: Values are for the printer without a print ribbon or retransfer ribbon.	
Ribbon Storage Requirements	Temperature 41° to 95° F (5° to 35° C) Humidity 45% to 85%  Important! For optimum results, make sure that Everest ribbons are stored within these ranges.	

Operating System Requirements	Windows-based PC Pentium 300 or better with 128MB RAM Windows XP Professional with SP2 or higher, Windows 2000 with SP4, or Windows Server 2003 USB port Macintosh computer G3 or better with 128 MB RAM Macintosh OS X version 10.3/10.4 USB port
--------------------------------------	---